

CLAIMS

1. A sand anchor, said anchor comprising;-
two or more substantially parallel tines mounted in spaced
relationship at respective first ends on a mounting member, said parallel
5 tines each having a second free tapered end;
attachment means for securing an anchor line thereto; and,
a compression member adjacent said first ends of said tines and
lying in a plane parallel to said tines.
2. An anchor as in claim 1 wherein the anchor comprises from three
10 to five tines.
3. An anchor as in claim 2 wherein the anchor comprises three tines.
4. An anchor as in claim 1 wherein the compression member
comprises a planar member extending transversely over upper forwardly
facing regions of said tines.
- 15 5. An anchor as claimed in claim 4 wherein the compression member
comprises the mounting member.
6. An anchor as in claim 4 wherein the compression member is
formed integrally with said mounting member.
7. An anchor as in claim 1 wherein the anchor includes a stabilising
20 member extending forwardly of said mounting member.
8. An anchor as in claim 7 wherein the stabilising member extends
substantially perpendicular to the plane of the tines.
9. An anchor as in claim 8 wherein the stabilising member is pivotally
attached to said mounting member for movement between a retracted
25 position adjacent said tines and an extended position substantially
perpendicular to the plane of said tines.
10. An anchor as in claim 9 wherein the stabilising member includes
the attachment means.
11. An anchor as in claim 10 wherein the stabilising member comprises
30 a plate-like member extending transversely of said mounting member.

12. An anchor as in claim 10 wherein the stabilising member comprises an arcuate member extending transversely of said mounting member.

264060" E44E2680